

FLUKE®

Calibration



5522A Multi-Product Calibrator

Robust, transportable
wide workload coverage

Wide workload coverage in the lab or in the field



5522A features at a glance

- Calibrates a wide variety of electrical test equipment
- Robust protection circuits prevent costly damage from operator error
- Redesigned carrying handles make the 5522A easy to transport
- Rugged carrying case with built-in handles and wheels and removable front/rear access doors for in-situ calibration in almost any environment
- Remarkably affordable





Multiple calibrators in one

The 5522A Multi-Product Calibrator addresses a wide calibration workload and comes with internal and external protection features that protect it against damage and make it easier to transport for on-site or mobile calibration. The 5522A can also be fully automated with MET/CAL® Plus Calibration Management Software. It is the ideal calibrator for metrology professionals who need to calibrate many different types of electronic equipment and want a transportable instrument that offers them a high return on investment.

The 5522A sources direct voltage and current, alternating voltage and current with multiple waveforms and harmonics, two simultaneous voltage outputs or voltage and current to simulate dc and ac power with phase control, resistance, capacitance, thermocouples and RTDs. The 5522A can also measure thermocouple temperature and pressure using one of 29 Fluke 700 Series pressure modules. Two options add the capability to calibrate oscilloscopes up to either 600 MHz or 1.1 GHz. And the 5520A-PQ Power Quality Option enables the 5522A to calibrate power quality instrumentation to the standards of the IEC and other regulatory agencies.

The 5522A calibrator covers many of the electronic test tools you use to keep your company up and running, including:

- Handheld and bench meters (analog and digital) up to 6½ digits
- Current clamps and clamp meters
- Thermocouple and RTD thermometers
- Process calibrators
- Data loggers
- Strip and chart recorders
- Watt meters
- Power harmonics analyzers
- Panel meters
- Graphical multimeters
- Power quality analyzers (with option)
- Analog or digital handheld and bench oscilloscopes to 600 MHz or 1.1 GHz (with options)
- ...and more, including pressure gauges and transducers and three-phase power meters

Calibrate almost anywhere, easily and dependably

Internal circuitry offers “mistake proof” protection

The 5522A provides reverse power protection, immediate output disconnection, and/or fuse protection on the output terminals for all functions. This protection is for applied external voltages up to ± 300 V peak.

Rugged carrying case enables safe transport and efficient onsite calibration

An innovative carrying case accessory makes it easier than ever to calibrate outside of the calibration laboratory, as well as inside. The shock-mounted case features built-in handles and wheels, enabling you to move the calibrator from place to place easily and safely.

The front and rear access doors are removable, so you can calibrate with the 5522A while its top, bottom and side panels remain protected—and avoid having to completely unpack and then re-pack the calibrator.

A redesigned front panel and ergonomic carrying handles make it easy to transport the calibrator short distances within the cal lab.





Powerful calibration solutions that are easy to use


The Fluke 5522A Multi-Product Calibrator makes it easy to get more work done.

It's intuitive design makes learning to operate it easy even for less experienced technicians, reducing references to the manual. For most tasks, your hand moves from left to right, keeping you from having to make long, illogical or uncomfortable movements. Most functions require minimal keystrokes.

The bright, backlit LCD display is easy to read from all angles and under a variety of light conditions.

Ergonomically designed, rugged handles make the 5522A easy to transport.

Temperature measurement modes calibrates thermocouple simulators and can also document environmental conditions present at the time of calibration, as required by all quality standards.



Spec menu lets you view the uncertainty for the present value.

Phase lock makes it easy to simulate three-phase power and enables current summing for high-current tests.


Internal circuitry plus overcurrent fuses protect against costly damage caused by electrical overloads accidentally applied to the calibrator's input terminals.

A rugged carrying case makes it easy to do onsite calibration. The front and back panels remove so you can use the calibrator without unpacking it.

An interface for Fluke 700 Series Pressure Modules, which are used to make precision measurements to calibrate pressure transducers and related instrumentation. Modules span various pressure ranges, as low as 0 to 10" H₂O (0 to 2.5 kPa), or as high as 0 to 10,000 psi (0 to 70,000 kPa).

Control output by pressing STBY and OPR keys.





Calculator-style keypad makes it easy to enter values.

Press the SCOPE key for on-demand oscilloscope calibration (optional).

Edit knob allows you to vary the output. When editing, the difference between the original output and the edited output is automatically computed and displayed in the control window.

The control window displays a variety of status messages, softkey menus, and status and other auxiliary information.

Soft keys allow access to the menus in the control windows, letting you select parameters such as offset, waveforms, phase, thermocouple or RTD type. PREV MENU lets you step backward through these menus.

MULT [X] and DIV [÷] keys simplify stepping up and down in decade multiples of any output setting, and let you step up or down to the next range in a 1-2-5 sequence for oscilloscope calibration.



Maximize your efficiency and your investment

Automate to increase throughput and efficiency

MET/CAL *Plus* software is a powerful application for creating, editing and testing calibration procedures and collecting and reporting results on a wide variety of instruments. It includes MET/CAL software—the industry leading software for automated calibration, and MET/TEAM™ Express—a dedicated system to manage your test and measurement assets. Or choose MET/TEAM standard edition for fully-featured enterprise calibration asset management, with optional modules for on-site calibration, commerce management, and customer web portal. Using MET/CAL *Plus* Calibration Management Software can help you meet the requirements for documented processes, procedures and reports mandated by most quality standards. Automating with MET/CAL software also helps you increase throughput and streamline your calibration processes.


Priority software support helps you stay productive

MET/SUPPORT Gold is an annual membership program offering premium support and services to help you stay as productive as possible with MET/CAL *Plus* software. Services include free software updates and upgrades, free access to the Fluke MET/CAL Warranted Procedures Library, plus discounts on training and custom procedure development. Members also receive invitations to regular calibration software web seminars and user group meetings. Use only a few of the Gold services and you can easily recover more than the cost of your membership fee.


Calibration and repair service

Fluke Calibration offers extensive calibration support and service to ensure your long-term satisfaction and return on investment in calibration equipment. Our worldwide network of calibration centers offers accredited calibrations traceable to national standards. We also offer fast, quality repair and calibration services including a module exchange program and full support in setting up your lab.

Time comparison for manual and automated calibration methods



Manual Cal with only pass/fail data Added time for Manual Cal with verified test data Automated Cal w/verified test data




Summary specifications

Function and range	
Direct volts	0 V to ± 1020 V
Direct current	0 A to ± 20.5 A
Alternating volts	1 mV to 1020 V 10 Hz to 500 kHz
Volt/hertz	1000 V @10 kHz/330 V @100 kHz
Alternating current	29 µA to 20.5 A 10 Hz to 30 kHz
Waveforms	Sine, square, triangle, truncated sine
Resistance	0 Ω to 1100 MΩ
Capacitance	220 pF to 110 mF
Power (phantom loads)	20.9 kW
Phase control	0.01°
Thermocouple (source and measure temperature)	B, C, E, J, K, L, N, R, S, T, U 10 µV/°C and 1 mV/°C
RTD (source temperature)	Pt 385-100 Ω, Pt 3926-100 Ω Pt 3916-100 Ω, Pt 385-200 Ω, Pt 385-500 Ω, Pt 385 1000 Ω, PtNi 385-120 Ω (Ni120), Cu 427 10 Ω
Interfaces	RS-232, IEEE 488
Phase lock	Yes
Frequency uncertainty	< 2.5 ppm
External frequency reference (10 MHz)	Yes
Oscilloscope calibrator (options)	Levelled sine wave from 5 mV to 5.5 Vpp max, frequencies 50 kHz to 600 kHz and 3.5 Vpp max to 1100 MHz; edge rise times of < 300ps, multiple trigger functions, lowest dc, square wave and timing uncertainty
Power Calibrator (options)	Composite harmonic, flicker simulation, sags and swells simulation modes


Metrology training increases skill levels

Calibration and metrology training from Fluke can help you and your staff become more knowledgeable in a wide variety of disciplines. Instructor-led classroom training is available for general topics in metrology, as well as for calibration software. On-site training can also be scheduled if you have a number of people in your organization who would benefit.

Fluke Calibration also offers other educational events such as web seminars and road shows on a wide variety of topics. The best way to stay informed about these events is to register to receive email and direct mail from Fluke Calibration. You can register online at www.flukecal.com.



Fluke Calibration multi-product calibrator family



Innovation from the leader in calibration

Fluke Calibration pioneered the multi-product calibrator concept, creating a family of instruments that allow you to calibrate the widest range of today's electronic test tools with a single instrument. These calibrators offer simple, portable, cost-effective solutions that allow you to match your calibrator to your workload and your budget.

Fluke Calibration is also recognized for its offerings in temperature, pressure, power, process, and rf calibration. Fluke Calibration provides the calibrators, standards, software, service, support and training you need for a complete solution in your cal lab.



5502A Multi-Product Calibrator 5080A High Compliance Multi-Product Calibrator

Calibration solutions that match your workload and budget

The 5502A is a versatile product that addresses a wide cross-section of your electrical calibration work load. It sources direct voltage and current, alternating voltage and current with multiple waveforms and harmonics, two simultaneous voltage outputs or voltage and current, and simulates power with phase control, resistance, capacitance, thermocouples and RTDs. The 5502A's Oscilloscope Calibration options provide level sine wave, fast edge, time mark and amplitude signals for calibration of oscilloscopes up to 600 MHz.

The 5502A was designed to cover a very wide range of medium accuracy electrical measurement devices including:

- Handheld and bench multimeters
- Oscilloscopes and ScopeMeter® Test Tools
- Wattmeters
- Analog volt/ohm/amp/watt instruments
- Electronic thermometers
- Data loggers
- Strip chart recorders
- XY Recorders
- Power harmonics analyzers
- Process calibrators
- Current clamps
- And related instruments

Calibration solutions for your analog and digital workload

The 5080A Multi-Product Calibrator calibrates your analog and digital workload accurately and economically. Its high voltage and current compliance makes analog workload calibration easy and precise. Built-in protection circuitry protects it against damaging input voltages.

This easy-to-use instrument calibrates a wide workload that includes:

- Analog meters
- Panel meters
- Digital multimeters
- Watt meters
- Clamp meters (with coil accessory)
- Megohm meters (optional)
- Oscilloscopes to 200 MHz (optional)
- ...and more

Versatile software applications enable you to record paperless results, and more.

Options and accessories expand workload coverage

Options and accessories enable you to use the 5080A to calibrate an even broader workload, including:

- Clamp meters—The 9100-200 10/50 turn coil and 5500A/COIL 50-turn current coil enables the 5080A to calibrate most popular clamp meters at currents up to 1000 A rms amps.
- Oscilloscopes—Calibrate oscilloscopes to 200 MHz quickly, easily, and cost effectively.
- Megohm meters—This option sources high ohms, high voltage resistors up to 18 GΩ. It also measures high voltage outputs.



Ordering information

Model

5522A	Multi-Product Calibrator
5522A/6	Multi-Product Calibrator with 600 MHz Oscilloscope Calibration Option
5522A/1GHZ	Multi-Product Calibrator with 1100 MHz Oscilloscope Calibration Option
5522A-PQ	Multi-Product Calibrator with Power Quality Option
5522A-PQ/6	Multi-Product Calibrator with Power Quality and 600 MHz Oscilloscope Calibration Options
5522A-PQ/1GHZ	Multi-Product Calibrator with Power Quality and 1100 MHz Oscilloscope Calibration Options

Accessories

5522A/CARRYCASE	Rugged Carrying Case with removable front/back panels
55XX/CASE	Transit Case with Wheels
5520A-525A/LEADS	Thermocouple and Test Lead Set
5500A/COIL	50-Turn Coil
5500A/HNDL	Side Handle
Y5537	Rack Mount Kit
Fluke-700Pxx	Pressure Module Series

Software

MET/CAL	MET/CAL Plus Calibration Management Software
MET/TEAM	MET/TEAM Test Equipment Asset Management Software

Other calibration solutions

Fluke Calibration provides the broadest range of calibrators and standards, software, service, support and training in electrical, temperature, pressure, RF and flow calibration.

Visit www.flukecal.com for more information about Fluke Calibration products and services.

Fluke Calibration. Precision, performance, confidence.™

Electrical	RF	Temperature	Pressure	Flow	Software
------------	----	-------------	----------	------	----------

Fluke Calibration
PO Box 9090,
Everett, WA 98206 U.S.A.

Fluke Europe B.V.
PO Box 1186, 5602 BD
Eindhoven, The Netherlands
Web access: <http://www.flukecal.eu>

For more information call:
In the U.S.A. (877) 355-3225 or Fax (425) 446-5116
In Europe/M-East/Africa +31 (0) 40 2675 200 or Fax +31 (0) 40 2675 222
In Canada (800)-36-FLUKE or Fax (905) 890-6866
From other countries +1 (425) 446-5500 or Fax +1 (425) 446-5116
Web access: <http://www.flukecal.com>

©2011, 2014 Fluke Corporation. Specifications subject to change without notice.
Printed in U.S.A. 9/2014 3931288b-en

Pub-ID 11704-eng

Modification of this document is not permitted without written permission from Fluke Corporation.